

05020628

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number  
**WO 2004/057535 A1**

(51) International Patent Classification<sup>7</sup>: **G06T 5/40, 5/00**

**Chi-Te** [US/US]; P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).

(21) International Application Number:  
PCT/IB2003/005966

(74) Common Representative: **KONINKLIJKE PHILIPS ELECTRONICS N.V.**; Intellectual Property & Standards, c/o BELK, Michael E., P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).

(22) International Filing Date:  
12 December 2003 (12.12.2003)

(25) Filing Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:  
60/435,237 20 December 2002 (20.12.2002) US

(71) Applicant (*for all designated States except US*): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **SHEN, Richard,**

[Continued on next page]

(54) Title: **ENHANCING VIDEO IMAGES DEPENDING ON PRIOR IMAGE ENHANCEMENTS**



(57) Abstract: A video stream containing encoded frame-based video information includes a first frame and a second frame. The encoding of the second frame depends on the encoding of the first frame. The encoding includes motion vectors indicating differences in positions between regions of the second frame and corresponding regions of the first frame, the motion vectors defining the correspondence between regions of the second frame and regions of the first frame. The first frame is decoded and a re-mapping strategy for video enhancement of the decoded first frame is determined using a region-based analysis. Regions of the decoded first frame are re-mapped according to the determined video enhancement re-mapping strategy for the first frame so as to enhance the first frame. The motion vectors for the second frame are recovered from the video stream and the second frame is decoded.

WO 2004/057535 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,  
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,  
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

**Declaration under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a  
patent (Rule 4.17(ii)) for all designations

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

## ENHANCING VIDEO IMAGES DEPENDING ON PRIOR IMAGE ENHANCEMENTS

The invention relates to the field of video image processing and more specifically to enhancing subsequent images of a video stream in which frames are encoded based on  
5 previous frames using prediction and motion estimation.

Those skilled in the art are directed to US6259472 and US5862254 which describe enhancing of video images. These citations are hereby incorporated herein in whole by reference.

In the invention herein, a video stream containing encoded frame based video  
10 information is received. The video stream includes an encoded first frame and an encoded second frame. The encoding of the second frame depends on the encoding of the first frame. More specifically, the encoding of the second frame includes motion vectors indicating differences in positions between regions of the second frame and corresponding regions of the first frame, the motion vectors define the correspondence between regions of  
15 the second frame and regions of the first frame.

The first frame is decoded and a re-mapping strategy for video enhancement of the decoded first frame is determined using a region-based analysis. Regions of the decoded first frame are re-mapped according to the determined video enhancement re-mapping strategy for the first frame so as to enhance the first frame.

20 The motion vectors for the second frame are recovered from the video stream and the second frame is decoded. Then regions of the second frame, that correspond to regions of the first frame, are re-mapped using the video enhancing, region-based, re-mapping strategy for the regions of the first frame so as to enhance the second frame.

The reuse of the video enhancing re-mapping strategy of previous frames for  
25 subsequent frames greatly reduces the processing required for providing video enhancements.

In a further aspect of the invention one or more regions of the second frame are selected depending on whether a similarity criteria is met for a similarity between the regions of the second frame and corresponding regions of the first frame. Then the re-  
30 mapping of the regions of the second frame based on the video enhancing region-based re-mapping strategy for the first frame is only performed for the selected regions of the second frame.

Limiting the reuse of the video enhancing re-mapping strategy of previous frames to only regions of the subsequent frames that are sufficiently similar to the previous frame, increases the likelihood that the subsequent frame will be enhanced.

5 A set top box using the decoder of the invention provides enhanced video pictures with minimal additional hardware costs. Using the decoder of the invention for a video disc player allows higher compression of groups of pictures on the video disc with the same perceived quality. A television that uses the decoder of the invention can display higher quality video pictures or utilize a more highly compressed video signal while providing the same quality as a less compressed signal.

10 Additional aspects and advantages of the invention will become readily apparent to those skilled in the art from the detailed description below with reference to the following drawings.

Figure 1 illustrates an example method of the invention for region-based enhancing of subsequent video images.

15 Figure 2 shows portions of an example decoder of the invention for providing region-based enhanced subsequent video images.

Figure 3 shows portions of a example set top box using the decoder of figure 2.

Figure 4 illustrates portions of an example DVD player using the decoder of figure 2.

20 Figure 5 shows portions of an example television using the decoder of figure 2.

In the following descriptions of the drawings, the same labels in different figures indicate similar devices. For convenience, such devices will only be described in detail in relation to the earliest described figure in which they appear.

Figure 1 shows a specific embodiment 100 of the method of the invention. In 102 a  
25 video stream is received. The stream contains encoded information for groups of pictures (GOP), the first picture in the GOP is an intra-coded frame (I-frame) and subsequent pictures in the GOP are non-I-frames. The decoding of the subsequent non-I-frames depends on the coding of the I-frame. The video stream may be, for example, an MPEG II stream of packets, in which case, the non-I-frames may be, for example, predicted frames  
30 (P-frames), and/or bi-directional frames (B-frames). However, any other type of GOP based video stream may be used as long as it contains subsequent frames that are encoded

based on previous frames. In 104, the I-frame is decoded. Decoding of I-frames is well known in the art.

5 In 106, a re-mapping strategy for re-mapping the intensity values to adjust the contrast is determined so as to enhance the decoded I-frame. The re-mapping strategy may use a region-based intensity analysis. Methods of determining re-mapping strategies for regions of decoded frames using such analysis are well known, and those skilled in the art are directed to US6259472 and US5862254 which disclose such re-mapping of intensity values. In 108, the intensity values of the decoded I-frame are re-mapped according to the determined re-mapping strategy.

10 In 108, motion vectors for the subsequent non-I-frame are recovered from the video stream as is well known in the art. Generally, motion vectors are differences in the positions between regions in an I-frame and corresponding regions in a non-I-frame that is coded dependent on the I-frame. The regions may be regions of similar intensity or regions of similar texture or any other predefined similarity between frames may be used to define regions.

15 In 110, DC coefficients for the subsequent non-I-frame are recovered from the video stream as is well known in the art. Generally, the DC coefficients are the differences between the values of the image blocks of the I-frame and the predicted values of corresponding image blocks of the non-I-frame, after motion estimation. Motion estimation is generally, the re-mapping of the regions depending on the motion vectors during decoding.

20 In 112, the intensity values in the regions of the non-I-frame are re-mapped depending on the re-mapping strategy of corresponding regions of the I-frame so as to adjust the contrast to enhance the non-I-frame. The correspondence between the regions is determined from the motion vectors.

25 If a region of the subsequent non-I-frame is more similar to the corresponding region of the I-frame (on which the decoding of the non-I-frame depends), than it is more likely that using the re-mapping strategy, developed for re-mapping the intensity values of the corresponding I-frame region, for re-mapping the intensity values for the non-I-frame region, will enhance the non-I-frame. On the other hand, if the region of the non-I-frame is substantially different than the corresponding region of the I-frame, then using the intensity value re-mapping strategy for the corresponding region of the I-frame, for re-mapping the

intensity values of the region of the non-I-frame, is not likely to enhance the non-I-frame, and in fact may even reduce the quality of the non-I-frame.

Using the strategy for re-mapping the I-frame for enhanced contrast for re-mapping subsequent frames greatly reduces the overhead required for contrast enhancement.

- 5 Generally any region-based video processing for improving the quality of an I-frame can be applied to corresponding regions of subsequent non-I-frames in a similar manner.

The re-mapping of the intensity values of the non-I-frame may also depend on the DC coefficients of the blocks of the regions of the non-I-frame on which the decoding of the non-I-frame depends. Generally, small values of the DC coefficients for a region  
10 indicate that the region is likely to be similar to the corresponding region in the I-frame after motion compensation. Thus, when its determined the DC coefficients are relatively large, then the re-mapping strategy for the intensity values of the I-frame are not used to re-map the intensity values of the non-I-frame. This can be determined by using a threshold for the DC coefficients, which can be a constant predetermined value or a variable value  
15 calculated for each region, and then using the I-frame re-mapping strategy to re-map the intensity values for a region only when the value of the DC coefficients are below the threshold. Those skilled in the art can easily determine either a standard predetermined DC coefficient threshold for regions in a frame, or a method to calculate a DC coefficient thresholds for each region in a frame, that can be used to enhance the frames. A useful DC  
20 coefficient threshold can be determined, for example, by a simple trial and error process of comparing frames in which different thresholds or threshold calculation methods have been applied.

In addition, the re-mapping of the intensity values of the non-I-frame may also depend on the properties of the motion vectors. As discussed above, the motion vectors are  
25 used to identify regions of the subsequent non-I-frame, that correspond to regions of the I-frame, in a process called motion compensation. However, in addition to their use in motion compensation, the properties of the motion vectors can also be used to determine the likelihood that the regions of the non-I-frame are similar to the corresponding regions of the I-frame.

30 Each motion vector has a value and a direction. Relationships between the motion vectors of neighboring regions include differences in values and differences in direction called orthogonality. Generally, for a non-I-frame, small values for the motion vector for a

region, small differences between motion vector values of a region and its neighboring regions, and small differences between motion vector directions of a region and its neighboring regions, each indicate that the region is more likely to be similar to the corresponding I-frame region.

5           Generally, a small value of the motion vector for a region of the non-I-frame indicates that the region is more likely to be similar to the corresponding region in the I-frame on which its decoding depends. When its determined the motion vector values are relatively large, then the re-mapping strategy for the intensity values of the I-frame is not used to re-map the intensity values of the non-I-frame. This can be determined by using a  
10           threshold for motion vector values, which can be a constant predetermined value or a variable value calculated for each region. Then the I-frame re-mapping strategy is used to re-map the intensity values for regions only if the values of the respective motion vectors for those regions are below the threshold. Again, those skilled in the art can easily determine either a standard predetermined motion vector value threshold for regions in the  
15           non-I-frame, or a method to calculate a motion vector value threshold for regions in a non-I-frame, that can be used to enhance the non-I-frames. A useful motion vector value threshold can be determined, for example, by a simple trial and error process of comparing non-I-frames in which different thresholds or threshold calculation methods have been applied.

20           Also, consistency in the values of the motion vectors between a region of the non-I-frame and its neighboring regions in the non-I-frame indicates that the region is more likely to be similar to the corresponding region in the I-frame on which the decoding of the non-I-frame depends. When its determined that the motion vector values of neighboring regions are substantially inconsistent or dissimilar to the motion vector values in the region, then  
25           the re-mapping strategy for the intensity values of the I-frame is not used to re-map the intensity values of the non-I-frame. This determination can be done, for example, by determining the average difference between the values of motion vectors for regions and the values of the motion vectors of neighboring regions, and then comparing the average differences in value to a value consistency threshold. The value consistency threshold can  
30           be a constant predetermined value or a variable value calculated for each region. Then the I-frame re-mapping strategy is used to re-map the intensity values for regions only if the average differences in the values of the motion vectors are below the value consistency

threshold. Similarly squares of the value differences or other combinations of the value differences or other well know statistical approaches could be used to determine value consistency. Again, those skilled in the art can easily determine either a standard predetermined value consistency threshold for regions in a frame, or a method to calculate value consistency thresholds for regions in a non-I-frame, that can be used to enhance the non-I-frames. A useful value consistency threshold may be determined, for example, by a simple trial and error process of comparing different non-I-frames in which different respective value consistency thresholds or threshold calculation methods have been applied.

Also, consistency of motion vector direction between a region and neighboring regions in the non-I-frame, indicate that the non-I-frame region is more likely be similar to the corresponding regions in the I-frame on which its decoding depends. When its determined that the motion vector direction of neighboring regions are substantially inconsistent or dissimilar to the motion vector direction of the region, then the re-mapping strategy for the intensity values of the I-frame for the region is not used to re-map the intensity values of the non-I-frame region. This can be determined, for example, by determining the average difference between the directions of motion vectors for regions and the directions of the motion vectors of neighboring regions, and then comparing the average differences in direction to a direction consistency threshold. The direction consistency threshold can be a constant predetermined value or a variable value calculated for each region. Then the I-frame re-mapping strategy is used to re-map the intensity values for regions only if the average differences in the values of the motion vectors are below the direction consistency threshold. Similarly squares of the direction differences or other combinations of the direction differences or other well know statistical approaches could be used. Again, those skilled in the art can easily determine either a predetermined value for the direction consistency threshold or a method to calculate such a threshold for each region in a frame, that can be used to enhance the non-I-frames. A useful direction consistency threshold or method to calculate such a threshold can easily be determined, for example, by a simple trial and error process of comparing frames in which different thresholds or threshold calculation methods are applied.

Multiple indications of similarity may be applied to determine whether to apply the re-mapping strategy of an I-frame to a subsequent non-I-frame whose decoding depends on

the I-frame. Those skilled in the art will know how to develop functions that combine multiple indications of similarity to determine whether to apply the I-frame re-mapping strategy to the non-I-frame. For example, they can use the I-frame contrast re-mapping strategy only when all the indications of similarity meet respective threshold requirements.

- 5 Alternatively or in addition, they can determine the differences or relative differences between the indications of similarity and their respective thresholds and only apply the I-frame contrast re-mapping strategy to the non-I-frame when the total of the differences or relative differences (or square of the differences or relative differences) is below a further threshold.

- 10 Those skilled in the art will know how to apply this process to more complex dependencies between frames such as subsequent non-I-frames, whose decoding is dependent on previous non-I-frames, whose decoding is dependent on I-frames. They can, for example, just apply the contrast enhancing re-mapping strategy of the I-frame to such subsequent non-I-frames. Alternatively, they can, for example, develop a second contrast enhancing re-mapping strategy for the previous non-I-frame, which can be applied to the  
15 subsequent non-I-frame.

The decoding of a non-I-frame may be dependent on multiple other frames. Those skilled in the art will know how to develop a function that applies the contrast enhancing re-mapping strategy of the multiple frames to the non-I-frame.

- 20 Figure 2 illustrates the basic components of a video decoder 120 of the invention.

A video stream of packets containing a group of pictures (GOP) is received at an input 122, the first picture in the GOP is an I-frame and a subsequent picture in the GOP is a non-I-frame. The video stream may be an MPEG stream as described above.

- A decoding unit 124 decodes the frames of the GOP. The decoding unit provides  
25 the decoded I-frame to a buffer 126, to a processing unit 128.

Processor 128 uses a region-based intensity analysis to determine a strategy to re-map intensity values to change contrast to enhance the I-frame image, and re-maps the intensity values of the I-frame in buffer 126 using the re-mapping strategy. The buffer then passes the contrast enhanced I-frame to output 132 through summation unit 130.

- 30 The decoding unit recovers the DC coefficients and the motion vectors for the subsequent non-I-frames of the GOP and supplies them to the buffer 126 and processor

128. Processor 128 re-maps the original I-frame and the contrast enhanced I-frame according to the motion vectors.

The decoding unit provides the decoded differences between the I-frame and the subsequent non-I-frames to the summation unit 130. Depending on a selection criteria, for each region, the buffer 126 supplies either the motion vector re-mapped I-frame or motion vector re-mapped contrast enhanced I-frame to summation unit 130. The summation unit combines the decoded differences and the re-mapped enhanced I-frame together to produce the decoded subsequent non-I-frame.

The selection criteria in this specific example for a region is as follows:

10  $DC < T1$ ; and  $MVV < T2$ ; and  $MVS < T3$ ; and  $MVO < T4$ ; and  
 $a1(DC - T1)^2 + a2(MVV - T2)^2 + a3(MVS - T3)^2 + a4(MVO - T4)^2 < T5$

Where DC is the value of the DC coefficients for the region; MVV is the motion vector value for the region; MVS is the average difference between the value of the motion vector and the value of the motion vectors of the regions above, below, and to each side of the region; and MVO is the orthogonality of the motion vector for the region with respect to the motion vectors of the regions that border the region; T1-T5 are predetermined thresholds; and a1-a4 are constants. The constants and thresholds were chosen statistically based on comparisons of results by viewers, to most consistently enhance the resulting image.

20 Figure 3 shows a set top box 140 of the invention. Tuner 142 selects a video stream for a video program from among multiple streams for several different video programs provided at input 144. The video decoder 120 of figure 2 decodes the video program and provides the decoded program to output 146 which can be directed to a video display e.g. a television set.

25 Figure 4 illustrates a DVD player 150 of the invention. The video player has a motor 152 for rotating a video disc 154. A laser 156 produces a radiation beam 158. A servo 160 controls the position of an optical system 162 to scan an information layer of the video disc with a focused spot of the radiation beam. The information layer effects the beam and reflects or transmits the beam to a radiation detector 164 for detecting the beam after it has been effected by the information layer. Processor 166 controls the servo and motor and produces a video stream containing encoded information for a group of pictures

(GOP) depending on the detection. Then the video decoder of figure decodes the video stream and supplies the decoded video stream to an output 168 for connection to a display.

The processor 166 can be the same processor 128 as in the decoder of figure 2 or an additional processor can be provided as shown.

5        Figure 5 shows a television 200 of the invention. A tuner 142 selects a video stream of a video program to be played from a plurality of video streams for respective video programs provided to input 144. The decoder 120 of figure 2 decodes the selected video program and provides it to display 206. The television may have components of the DVD player of figure 4 for playing stored video programs (or recording programs) using the  
10    DVD components.

The invention has been described above in relation to specific example embodiments. Those skilled in the art will know how to modify these example embodiments within the scope of the invention herein. The scope of the invention is only limited by the following claims.

## CLAIMS:

1. A method, comprising  
receiving a video stream containing encoded frame based video information including an encoded first frame and an encoded second frame, the encoding of the second frame depends on the encoding of the first frame, the encoding of the second frame includes motion vectors indicating differences in positions between regions of the second frame and corresponding regions of the first frame, the motion vectors define the correspondence between regions of the second frame and corresponding regions of the first frame;  
decoding the first frame;  
determining a re-mapping strategy for video enhancement of the decoded first frame using a region-based analysis;  
re-mapping regions of the decoded first frame according to the determined video enhancement re-mapping strategy for the first frame so as to enhance the first frame;  
recovering from the video stream, the motion vectors for the second frame;  
decoding the second frame;  
re-mapping regions of the second frame that correspond to regions of the first frame using the video enhancing re-mapping strategy for the first frame so as to enhance the second frame.
2. The method of claim 1, wherein:  
the first frame is an I-frame and the second frame is a subsequent non-I-frame.
3. The method of claim 2, wherein:  
the video stream is an MPEG stream of packets; and  
the non-I-frame is a P-frame or a B-frame.
4. The method of claim 1, wherein:  
the video enhancement re-mapping strategy for the first frame includes re-mapping intensity values to adjust the contrast to enhance the first frame.

5. The method of claim 1, wherein:
  - the decoding of the second frame is performed using a reconstruction loop; and
  - the video enhancement re-mapping of the second frame is done completely within the reconstruction loop so that motion vectors do not have to be stored.
6. The method of claim 1, wherein:
  - the method further comprises selecting one or more regions of the second frame depending on whether a similarity criteria is met for a similarity between the regions of the second frame and corresponding regions of the first frame, the similarity criteria including measures of similarity in addition to correspondence between regions of the first frame and second frame; and
  - the re-mapping of the regions of the second frame based on the video enhancement re-mapping strategy for the first frame is only performed for the selected regions of the second frame.
7. The method of claim 1, wherein:
  - the method further comprises recovering from the video stream, values of DC coefficients for the second frame, the DC coefficient values being the differences between the first frame and the second frame, in the predicted values of image blocks, after motion compensation, motion compensation being the re-mapping of regions depending on the motion vectors during decoding; and
  - the method further comprises selecting regions of the second frame depending on whether the values of the DC coefficients for the regions meet a similarity criteria; and
  - the re-mapping of the regions of the second frame based on the video enhancement re-mapping strategy for the first frame is only performed for the selected regions of the second frame.
8. The method of claim 7, wherein:
  - the selection of regions of the second frame for re-mapping based on the video enhancement re-mapping strategy for the first frame, depends on the relation between the

values of the DC coefficients for blocks of the region of the second frame and a predetermined or calculated DC coefficient threshold;

9. The method of claim 1, wherein:

the method further comprises selecting regions of the second frame depending on the respective values of motion vectors for the regions; and

the re-mapping of the regions of the second frame based on the video enhancement re-mapping strategy for the first frame is only performed for the selected regions of the second frame.

10. The method of claim 1, wherein:

the method further comprises selecting regions of the second frame depending on whether the regions meet a similarity criteria depending similarity between the properties of the motion vectors for the region and the properties of the motion vectors for neighboring regions of the respective regions; and

the re-mapping of the regions of the second frame based on the video enhancement re-mapping strategy for the first frame is only performed for the selected regions of the second frame.

11. The method of claim 10, wherein:

the properties of the motion vectors on which meeting the similarity criteria depends includes the similarity between the value of the motion vector for a region and the motion vectors for its neighboring regions.

12. The method of claim 10, wherein:

the properties of the motion vectors on which meeting the similarity criteria depends includes the orthogonality between the value of the motion vector for a region and the motion vectors for its neighboring regions.

13. The method of claim 1, wherein:

the first frame is an I-frame and the second frame is a subsequent non-I-frame;

the video stream is an MPEG stream of packets and the non-I-frame is a P-frame or a B-frame;

the video enhancement re-mapping strategy for the first frame includes re-mapping intensity values to adjust the contrast to enhance the first frame;

the method further comprises selecting one or more regions of the second frame depending on whether a similarity criteria is met for a similarity between the regions of the second frame and corresponding regions of the first frame and the re-mapping of the regions of the second frame based on the video enhancement re-mapping strategy for the first frame is only performed for the selected regions of the second frame;

the method further comprises recovering from the video stream, values of DC coefficients for the second frame, the DC coefficient values being the differences between the first frame and the second frame, in the predicted values of image blocks, after motion compensation, motion compensation being the re-mapping of regions depending on the motion vectors during decoding; and the meeting of the similarity criteria depends on the values of the DC coefficients;

the meeting of the similarity criteria depends on comparing the properties of the motion vectors for the regions and neighboring regions of respective regions;

the properties of the motion vectors on which meeting the similarity criteria depends includes the similarity between the value of the motion vector for a region and the motion vectors for its neighboring regions;

the properties of the motion vectors on which meeting the similarity criteria depends includes the orthogonality between the value of the motion vector for a region and the motion vectors for its neighboring regions.

14. A video decoder, comprising:

an input for receiving a video stream containing encoded frame based video information including an encoded first frame and an encoded second frame, the encoding of the second frame depends on the encoding of the first frame, the encoding of the second frame includes motion vectors indicating differences in positions between regions of the second frame and corresponding regions of the first frame, the motion vectors define correspondence between regions of the second frame and corresponding regions of the first frame;

a decoding unit for decoding the frames, the decoding unit recovers the motion vectors for the second frame;

processing means for determining a re-mapping strategy for video enhancement of the decoded first frame using a region-based analysis, and for re-mapping the first frame using the re-mapping strategy, and for re-mapping one or more regions of the second frame depending on the re-mapping strategy for corresponding regions of the first frame.

15. The decoder of claim 14 wherein:

the decoder further comprises a buffer;

the decoding unit decodes the first frame and stores the first frame in the buffer;

the processing means re-maps the stored first frame according to the video enhancement re-mapping strategy, and transmits the enhanced first frame;

the decoder further comprises a combiner;

the decoding unit decodes the second frame to determine the differences between the first frame and the second frame, and transmits the differences to the combiner;

the processor again re-maps the intensity values of the first frame depending on the motion vectors of the second frame and transmits the again re-mapped first frame to the combiner;

the combiner combines the again re-mapped first frame with the differences between the first frame and the second frame to produce a decoded second frame that is enhanced.

16. The decoder of claim 14, wherein:

the processing means selects one or more regions of the second frame depending on whether a similarity criteria is met for a similarity between the regions of the second frame and corresponding regions of the first frame; and

the processing means re-maps the regions of the second frame based on the video enhancement re-mapping strategy for the first frame only for the selected regions of the second frame.

17. The decoder of claim 14 in which the processing means operates the decoding unit.

18. A set-top-box, comprising:  
a tuner for selecting a video stream of a video program to be played from a plurality of video streams for multiple video programs;  
the video decoder of claim 14 for decoding the selected video stream; and  
an output for providing the decoded program to a video display.
19. A video disc player, comprising:  
a motor for rotating the disc;  
a laser for producing a radiation beam;  
an optical system for scanning an information layer of the video disc with the radiation beam, the information layer effecting the beam;  
a servo for positioning the optical system;  
a radiation detector for detecting beam after it has been effected by the information layer;  
processor means to control the servo and motor and to produce a video stream containing encoded information for a group of pictures (GOP) depending on the detection;  
and  
the video decoder of claim 13.
20. A television, comprising:  
a tuner for selecting a video stream of a video program to be played from a plurality of video streams for multiple video programs;  
the video decoder of claim 14 for decoding the selected video stream; and  
a video display for displaying the decoded frames of the selected video program.
21. A method comprising:  
receiving a video stream containing encoded information for groups of pictures (GOP), the first picture in a GOP is an I-frame, and a subsequent picture in the GOP is a non-I-frame;  
decoding the I-frame;

determining a re-mapping strategy of intensity values to change the contrast to enhance the decoded I-frame using a region-based intensity analysis;

re-mapping the intensity values of the decoded I-frame according to the determined re-mapping strategy;

recovering from the video stream, motion vectors for the subsequent non-I-frame, the motion vectors are differences in the positions of regions in the I-frame and corresponding regions in the non-I-frame;

decoding the subsequent non-I-frame;

determining whether the similarity between corresponding regions meet a similarity criteria;

selecting one or more regions of the non-I-frame depending on whether similarity criteria is met for a similarity between the regions of the non-I-frame and the corresponding regions of the I-frame;

re-mapping the intensity values of the selected regions of the non-I-frame depending on the re-mapping strategy of the corresponding regions of the I-frame so as to change the contrast to enhance the non-I-frame.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

## INTERNATIONAL SEARCH REPORT

Internatio  
plication No  
PCT/IB 03/05966A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G06T5/40 G06T5/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 G06T H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EP0-Internal, WPI Data, PAJ, INSPEC, IBM-TDB

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 157 396 A (FOGG CHAD ET AL) 5 December 2000 (2000-12-05) abstract column 5, line 18 - line 58	1-21
A	ATZORI L ET AL: "Post-processing for real-time quality enhancement of MPEG-coded video sequences" MULTIMEDIA AND EXPO, 2000. ICME 2000. 2000 IEEE INTERNATIONAL CONFERENCE ON NEW YORK, NY, USA 30 JULY-2 AUG. 2000, PISCATAWAY, NJ, USA, IEEE, US, 30 July 2000 (2000-07-30), pages 975-978, XP010513172 ISBN: 0-7803-6536-4 the whole document	1-21

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

26 March 2004

Date of mailing of the international search report

06/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Herter, J

## INTERNATIONAL SEARCH REPORT

Internatic      pplication No  
PCT/IB 03/05966

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	BOYCE J ET AL: "LOW-COST ALL FORMAT ATV DECODING WITH IMPROVED QUALITY" SMPTE ADVANCED MOTION IMAGING CONFERENCE, XX, XX, 2 February 1996 (1996-02-02), pages 45-51, XP001006067 the whole document	1-21
A	US 6 385 248 B1 (SAZZAD SHARIF M ET AL) 7 May 2002 (2002-05-07) abstract; figure 4 column 4, line 30 - column 5, line 35	1-21
P,A	US 2003/206591 A1 (BOROCZKY LILLA ET AL) 6 November 2003 (2003-11-06) abstract; figures 5-8 paragraph '0007! - paragraph '0010! paragraph '0018! - paragraph '0020!	1-21
A	US 6 259 472 B1 (PARK YUNG-JUN) 10 July 2001 (2001-07-10) cited in the application the whole document	1-21
A	US 5 862 254 A (CHO YONG-HUN ET AL) 19 January 1999 (1999-01-19) cited in the application the whole document	1-21

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

Internatio      ublication No  
PCT/IB 03/05966

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6157396	A	05-12-2000	WO 0010129 A1	24-02-2000
US 6385248	B1	07-05-2002	US 6122321 A	19-09-2000
			WO 9959343 A1	18-11-1999
			JP 2002515705 T	28-05-2002
			US 6148032 A	14-11-2000
US 2003206591	A1	06-11-2003	WO 03094111 A1	13-11-2003
US 6259472	B1	10-07-2001	KR 189922 B1	01-06-1999
			CN 1193399 A ,B	16-09-1998
			DE 19780478 T0	05-11-1998
			GB 2321817 A ,B	05-08-1998
			JP 3046079 B2	29-05-2000
			JP 10510939 T	20-10-1998
			WO 9749064 A1	24-12-1997
US 5862254	A	19-01-1999	KR 213039 B1	02-08-1999
			KR 176602 B1	01-05-1999
			CN 1162799 A ,B	22-10-1997
			DE 69716803 D1	12-12-2002
			DE 69716803 T2	27-03-2003
			EP 0801360 A2	15-10-1997
			ES 2185874 T3	01-05-2003
			JP 3130268 B2	31-01-2001
			JP 10032769 A	03-02-1998